

# UNITED STATES PATENT AND TRADEMARK OFFICE

UNIVER STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMANSIONER FOR PATENTS AO Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/036,333	12/24/2001	William D. Slyva	EMC01-41(00024)	3305
75	90 10/10/2006		. EXAM	INER
Barry W. Chapin, Esq.			HERRING, VIRGIL A	
CHAPIN & HU	ANG, L.L.C.			
Westborough Office Park 1700 West Park Drive Westborough, MA 01581			ART UNIT	PAPER NUMBER
			2132	
			DATE MAILED: 10/10/2006	

Please find below and/or attached an Office communication concerning this application or proceeding.

•		Application No.	Applicant(s)			
Office Action Summary		10/036,333	SLYVA ET AL.			
		Examiner	Art Unit			
		Virgil Herring	2132			
	The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply					
A SH WHIC - Exter after - If NO - Failu Any r	ORTENED STATUTORY PERIOD FOR REPLY CHEVER IS LONGER, FROM THE MAILING DATES and the may be available under the provisions of 37 CFR 1.13 SIX (6) MONTHS from the mailing date of this communication. Period for reply is specified above, the maximum statutory period were to reply within the set or extended period for reply will, by statute, reply received by the Office later than three months after the mailing and patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION  16(a). In no event, however, may a reply be time  rill apply and will expire SIX (6) MONTHS from the  cause the application to become ABANDONE	l. ely filed the mailing date of this communication. 0 (35 U.S.C. § 133).			
Status						
2a)	Responsive to communication(s) filed on <u>20 Ju</u> This action is <b>FINAL</b> . 2b) This Since this application is in condition for allowan closed in accordance with the practice under <i>E</i>	action is non-final.  see except for formal matters, pro				
Dispositi	on of Claims					
5)□ 6)⊠ 7)□	Claim(s) <u>1-5,7-19,21-29,31-41,43-47,49-53,55-4a</u> ) Of the above claim(s) is/are withdraw Claim(s) is/are allowed. Claim(s) <u>1-5,7-19,21-29,31-41,43-47,49-53,55-64</u> Claim(s) is/are objected to. Claim(s) are subject to restriction and/or	vn from consideration. <u>57 and 59-63</u> is/are rejected.	e application.			
Applicati	on Papers					
10)	The specification is objected to by the Examiner The drawing(s) filed on is/are: a) acce Applicant may not request that any objection to the o Replacement drawing sheet(s) including the correcti The oath or declaration is objected to by the Example.	epted or b) objected to by the Edrawing(s) be held in abeyance. See on is required if the drawing(s) is obj	37 CFR 1.85(a). ected to. See 37 CFR 1.121(d).			
Priority u	nder 35 U.S.C. § 119					
<ul> <li>12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).</li> <li>a) All b) Some * c) None of:</li> <li>1. Certified copies of the priority documents have been received.</li> <li>2. Certified copies of the priority documents have been received in Application No.</li> <li>3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).</li> <li>* See the attached detailed Office action for a list of the certified copies not received.</li> </ul>						
Attachment	t(s) e of References Cited (PTO-892)	4) 🔲 Interview Summary	(PTO-413)			
2) Notice 3) Inform	e of Draftsperson's Patent Drawing Review (PTO-948) nation Disclosure Statement(s) (PTO/SB/08) r No(s)/Mail Date	Paper No(s)/Mail Da 5) Notice of Informal Pa 6) Other:	te			

#### **DETAILED ACTION**

This action is responsive to the Request for Continued Examination filed 20 July 2006. Claims 1-5, 7-19, 21-29, 31-41, 43-47, 49-53, 55-57, and 59-63 are currently pending. Claims 61-63 are new.

#### Response to Arguments

Applicant's arguments filed 20 July 2006 have been fully considered but they are not persuasive.

Applicant argued that Wookey (US Patent #6,023,507) discloses analog modem-based communications rather than digital packet-based communications. The examiner agrees with this point, but the argument is not persuasive to overcome the rejection because the present claims indicate that modems communicate digitally using packets. Note figure 1, #140 and page 22 of the specification of the present application.

Modems are included in the applicant's definition of "data communication device". As such, according to applicant's disclosure, the data communications device establishing packet communications systems as described in the claims encompasses modems, and therefore the disclosure of Wookey is applicable.

### Claim Rejections - 35 USC § 112

The following is a quotation of the first paragraph of 35 U.S.C. 112:

The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the

Application/Control Number: 10/036,333

Art Unit: 2132

art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

Claims 61-63 are rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the written description requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to reasonably convey to one skilled in the relevant art that the inventor(s), at the time the application was filed, had possession of the claimed invention. Claims 61-63 are directed to establishing an IP digital packet communications session. Applicant asserts that support for this amendment can be found in the specification at page 22, lines 5-17. Page 22, lines 3-17 are quoted below:

The connection establishment computer systems 130 can include a number of different computer systems and components that support various authentication, authorization and communications handshaking functions (e.g., connection establishment protocols and handshaking techniques defined by embodiments of the invention) as will be explained in detail. The data communications devices 140 can include one or more routers, modems and/or gateway firewall devices that provide data communications functionality and security between the vendor computer network 110 and other networks such as the wide area network 115 and customer computer networks 120, as will be explained shortly.

In this example, only one vendor computer network 110 is illustrated. It is to be understood that multiple vendor computer networks 110 can be configured according to embodiments of the invention and can be physically coupled to a wide area network 115 such as a circuit switched network such as a PSTN and/or to a computer network such as the Internet, for example, at various locations throughout the world.

Two customer computer networks 120-1 (operated by CUSTOMER A) and 120-

Clearly, there is no support for the phrase "IP digital communications session" in lines 5-17. The examiner could not find support for this limitation anywhere in the specification.

### Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

Claims 1-5, 7-19, 21-29, 31-41, 43-47, 49-53, 55-57, and 59-63 are rejected under 35 U.S.C. 102(b) as being anticipated by Wookey (US Patent #6,023,507).

With regards to claims 1, 25, 47, 49, and 56, Wookey discloses in a computer system, a method for establishing a packet communication sessions to a data storage system, the method comprising the steps of:

receiving a request to establish a communications session with a data storage system; (Col. 1, Lines 37-38: "the user of that computer system calls the remote service center.")

establishing a first packet communications session from the computer system to a data communications device capable of communicating with the data storage system, the establishing a first packet communications session comprising:

obtaining connection information for a data communications device that is capable of communicating with the data storage system; (Col. 9, Lines 4-5; If communications are always initiated from the service center, the service center must have the connection information for a data communications device stored somewhere on-site)

initiating the first packet communications session from the computer system to a data communications device using the connection information for the data communications device; (Col. 9, Lines 4-5)

providing, to the data communications device, first packet communications session authentication information such that the data communications device can determine if a user of the computer system is authorized to establish the first packet communications session, and (Col. 9, Lines 41-43)

if the user of the computer system is authorized to establish the first packet first packet communications session, allowing the computer system to perform the step of establishing a second packet communications session from the data communications device to the data storage system; and (Col. 9, Lines 41-43; If the password for the customer modem is accepted, it will open the second connection from the modem to the customer's monitored system)

if the user of the computer system is not authorized to establish the first packet first packet communications session, denying the ability of the computer system to perform the step of establishing a second packet communications session from the data communications device to the data storage system; (Col. 9, Lines 41-43; Conversely, if the password for the

customer modem is not accepted, the second connection from the modem to the customer's monitored system would not be opened)

establishing a second packet communications session from the data communications device to a service processor associated with the data storage system; (Col. 9, Lines 41-43; The service center first negotiates the connection with the customer modem before a connection between the modem and the monitored system is established)

and

performing packet communications between the computer system and the service processor associated with the data storage system using the first and second packet communications sessions. (Inherent; The communications connection between the service center and monitored system would be non-functional if packet communications were not performed)

With respect to claims 2 and 26, Wookey (507) discloses the method of claim 1 or 25 wherein the step of receiving a request to establish a communications session with a data storage system comprise the steps of:

receiving user authentication for a user of the computer system;

authenticating an identity of the user based on the user

authentication information;

receiving a data storage system identity indicating an identity of the data storage system to which the packet communications session is to be established.

In column 8, lines 42-45 Wookey (507) states that "It is possible to protect each monitor with a unique password so that only authorized administrative personnel can access a given monitor for modification." Wookey (507) discloses a system for remotely servicing multiple computer systems in which service personnel can receive information on which systems need service and then securely connect using established authentication techniques.

With respect to claims 3 and 27, Wookey (507) discloses the method of claim 2 or 26 wherein:

the request to establish a communications session with a data storage system includes the identity of the data storage system to which a communications session is to be established; and

wherein the identity specifies at least one of:

- i) a phone number of a service processor modem associated with the data storage system; (Col. 9, Lines 40-45)
- ii) a serial number of the data storage system; and (Col. 4, Lines 63-68)

iii) customer information related to a customer operating the data storage system. (Col. 4, Lines 63-68)

With respect to claims 4 and 28, Wookey (507) discloses the method of claim 2 or 26 wherein the step of receiving data storage system identity information comprises the steps of:

receiving data storage system search criteria;

providing data storage system search criteria to a connection monitor computer system to produce a set of data storage system identities that meet the data storage system search criteria; and

receiving the set of data storage system identities that meet the data storage system search criteria; and

allowing the user to select at least one data storage system identity from the set of data storage system identities.

Wookey (507) discloses that at startup, administration software searches for all monitor software on the same subnet (Col. 13, Lines 13-20). Thus, the criterion of the search is simply "all computers connected to this computer." This criterion is received from the administrator program code when the process begins to execute. The administrator software then displays a list of the accessible computers available for servicing, so that the user can select one to connect with (Fig. 8).

With respect to claims 5 and 29, Wookey (507) discloses the method of claim 4 or 28 wherein:

the data storage system search criteria is received from at least one of:

i) a user of the computer system;

ii) a service ticket identifying a data storage system;

the data storage system search criteria includes at least a portion of the user authentication information; and

the set of data storage system identities that meet the data storage system search criteria includes identities of data storage systems to which a user identified by the portion of the user authentication information is allowed to establish a packet communications session.

Since the invention of Wookey (507) searches for all connected computers when the administrator software starts running, one can say that the user supplies the search criteria by selecting which computers are on the same subnet as the computer running the administrator program (Col. 13, Lines 13-20). It is implicit that a program to inform the user of errors in the connected computers will apprise the user of any errors discovered (in other words; presenting a service ticket to the user). Wookey (507) discloses, in lines 50-54 of column 10, that the diagnostic data of the connected computers is password protected so that nobody other than a qualified service center engineer can access the information. Thus, since the search criteria are determined by physical connections (hard-wired) to the service computer, and access to the service

Application/Control Number: 10/036,333

Art Unit: 2132

computer is restricted by an authentication control subsystem, it is possible to state that the user authentication is a part of the search criteria because the user authentication is a component of one of the computers in the network which defines the search criteria.

With respect to claims 7 and 31, Wookey (507) discloses the method of claim 1 or 25 wherein the step of obtaining connection information for the data communications device comprises the steps of:

providing, to a connection monitor computer system, a request for an address of a data communications device, the request including data communications device selection criteria allowing the connection monitor computer system to select and return an address of an available data communications device that is authorized to establish the second packet communications session to the data storage system; and (Col. 4, Lines 47-53)

receiving the address of the data communications device selected by the connection monitor computer system. (Col. 4, Lines 47-53)

Wookey (507) discloses one modem (data communications device) for each small network of customer computer systems. Column 9, lines 40-41 indicate that the computer at the service center stores customer modem connection information in its internal memory. In this situation, a request for the address of the data communications device would take the form of a command to read from the hard drive or RAM.

With respect to claims 8 and 32, Wookey (507) discloses the method of claim 7 or 31 wherein the request for an address of the data communications device includes at least one of:

- i) a portion of the user authentication information; (Col. 8, Lines 42-45)
- ii) customer information concerning a customer operating the data storage system; and (Col. 4, Lines 62-65)
- iii) connection information associated with the data storage system; and (Col. 4, Lines 62-65)

wherein the connection monitor computer system compares the request for an address against user and customer data to determine what data storage systems a user providing the request is allowed to access. (Col. 8, Lines 42-45)

Wookey (507) explains in column 8 that "it is possible to protect each monitor with a unique password so that only authorized administrative personnel can access a given monitor for modification." Protection with a unique password implies the use of user authentication information. Additionally, connection information associated with the system to which the user is attempting to connect would be inherently required. It is known to those in the art that connection authorization will involve comparing user data with data associated with the remote system. In this case, that would mean comparing the administrator's user data with the customer's information to determine if the administrator is authorized to modify that customer's monitor.

Art Unit: 2132

With respect to claims 9 and 33, Wookey (507) discloses the method of claim 1 or 25 wherein:

the step of initiating the first packet communications session establishes an internet protocol communications session between the computer system and the data communications device; and (Col.4, Lines 47-50)

wherein the step of providing, to the data communications device, first packet communications session authentication information passes user authentication information from the computer system to the data communications device to allow the data communications device to authorize the internet protocol communications session. (Col. 8, Lines 42-45)

In column 4, Wookey (507) discloses that the modems of the vendor's modem pool are configured to connect to modems of the customer's monitored systems, and that the connection is under the control of a network terminal server. Thus, he has a communications session between a computer system and a data communications device. Since another connection between the data communications device and the monitored system exists implicitly, the connection from the vendor computer system to the data communications device can be described as the first packet communications session. Similarly, the connection from the data communications device is the second packet communications session. In column 8, Wookey (507) discloses the protection of

the monitored computer systems using a unique password. A password implies authentication of the user at some point in the connection setup process. Authenticating the user to the remote network's server (the data communications device) is a well-known step in internet protocol communications.

Page 13

With respect to claims 10 and 34, Wookey (507) discloses the method of claim 9 wherein the step of providing, to the data communications device, first packet communications session authentication information causes the data communications device to communicate with a user account computer system to verify if the user of the computer system identified in the user authentication information is authorized to cause the data communications device to establish the first and second packet communications sessions from the computer system, through the data communications device, to the data storage system. (Col. 8, Lines 42-45)

Because the data communications device is a router or modem, a list of valid users would have to be stored elsewhere, because routers and modems have very little internal memory, which is used only to store the device's firmware and a list of valid IP addresses, or conversely, a list of blocked IP addresses. Thus, a separate computer system, which contains a list of valid users and their passwords, must exist inherently, and the data communications device must be able to communicate with it.

With respect to claims 11, 35, and 50, Wookey (507) discloses the method of claim 1 or 25 or 47 wherein the step of establishing a second packet communications session from the data communications device to the data storage system comprises the steps of:

providing, to the data communications device, second packet communications session connection information allowing the data communications device to initiate the second packet communications session from the data communications device to the data storage system; (Col. 4, Lines 47-50)

receiving second packet communications session state information indicating a state of the second packet communication session between the data communications device and the data storage system.

(Col. 9, Lines 52-65)

In column 4, Wookey (507) discloses the connection of the vendor modem to a customer modem under the control of a network terminal server. This clearly shows a first packet communications session from the vendor modem to the server, and a second packet communications session from the server to the customer modem. In this case, the network terminal server is acting as a router (data communications device). Those skilled in the art will recognize that in order to establish the connection between the router and the customer computer the user wishes to access, the router must be provided session information indicating to which computer the connection should be

made. Column 9 shows the login and verification process for the connection. It is inherent that if verification is being carried out, then all parties involved in the verification are aware of it. Thus, at some point the data communications device must have received second packet communications session state information, which it would pass on to the vendor computer.

With regards to claims 12 and 36, Wookey (507) discloses the method of claim 11 or 35 wherein:

the second packet communications session connection information includes data storage system connection information associated with the data storage system and user authentication information of the user of the computer system; and (Col. 9, Lines 52-55)

wherein the step of providing the second packet communications session connection information to the data communications device causes the data communications device to perform the steps of:

initiating the second packet communications session from the data communications device to the data storage system using the data storage system connection information; (Col. 9, Lines 52-55)

providing the user authentication information to a remote access server associated with the data storage system to allow the remote access server to authorize the establishment of the second packet communications session from the data communications device to the data storage system; (Col. 8, Lines 42-48)

receiving data storage system address information at the data communications device identifying an address of the data storage system to allow the data communications device to establish the second packet communications session; and (Col. 9, lines 52-55)

forwarding second packet communications session state information to the computer system from the data communications device to allow the computer system to perform packet communications between the computer system and data storage system using the first and second packet communications sessions. (Col. 9, Lines 52-55)

It is inherent to the system that the second packet communications session, between a router and the customer computer, must contain connection information for the customer computer. If it did not, the router would not know to which computer the user wishes to connect. Additionally, the inclusion of the user authentication information would be inherent, because without that information the customer computer would not know if the person attempting to establish a connection is a valid administrator. The steps listed in the connection procedure are also inherent requirements. Initiating the second packet communications session is inherent because that was the whole purpose of the connection process. Providing the user authentication information to a remote access server associated with the data storage system is inherent because that

Application/Control Number: 10/036,333

Art Unit: 2132

is the reason for having the user authentication information. Were it not provided to a

server tasked to verification of remote users, then the data storage system would have

no way of knowing if the user information is valid. The data communications device

must inherently receive data storage system address information so that it can be sure

that the correct connection was made. Finally, forwarding the second packet

communications session state information to the vendor's computer system is inherent

because if the state information were not forwarded, the vendor's computer system

would have no way of knowing if the connection to the data storage system was

successful.

With respect to claims 13, 37, and 51, Wookey (507) discloses the method of

claim 12 or 36 or 50 wherein the data storage system address information is a pre-

configured network address assigned to the service processor associated with the data

storage system.

Though it is never named as such, Wookey (507) inherently discloses the data

storage system address information. It is known to those in the art that any computer

system on a network or the Internet will always have an IP address or a modem phone

number, which is the address of the computer on the network.

With regards to claims 14 and 38, Wookey (507) discloses the method of claim

12 or 36 wherein:

the second packet communications session connection information includes data storage system connection information including a phone number of a service processor modern associated with the service processor associated with the data storage system; and (Col. 4, Lines 46-68)

wherein the step of initiating the second packet communications session from the data communications device to the data storage system causes the data communications device to instruct a modem to dial the phone number of a service processor modem in order to establish a dial up connection to the data storage system from the data communications device. (Col. 4, Lines 47-49)

Wookey (507) discloses a dialup connection between the vendor's computer system and a monitoring computer connected to one or more monitored systems. It is known to those in the art that in the process of communicating between the vendor's computer and the monitoring computer, packet communication sessions are established between the vendor computer, a router (data communications device) and the monitoring computer. If the vendor's modem is to dial the customer's modem, the phone number of the customer's modem is an inherent part of the information which must be transferred.

With respect to claims 15 and 39, Wookey (507) discloses the method of claim 12 or 36 wherein:

the second packet communications session state information includes the data storage system address information and includes data storage system

connection bandwidth information; and

wherein the step of forwarding second packet communications session state information to the computer system from the data communications device causes the data communications device to perform the step of:

forwarding the second packet communications session state information to a network manager computer system which receives the second packet communications session state information and forwards routing information to the computer system so that the computer system can perform packet communications with the data storage system. (Col. 4, Lines 49-52)

It is known to those in the art that communications session information is passed between two computers that are attempting to communicate with each other. This state information includes the address information for all involved computers, as well as connection speed information (bandwidth). If this information is not provided the computers will not have the knowledge necessary to communicate correctly. Wookey (507) discloses a connectivity server 304 that manages connections to the modem pool 301 inside the service center 101. One skilled in the art would recognize that a server that provides links to a modem pool would receive communications session information before finalizing the link between the vendor's computer and the service center modem pool.

With respect to claims 16, 40, and 52, Wookey (507) discloses the method of claim 12, 35, or 47 wherein the step performing packet communications between the computer system and the service processor associated with the data storage system comprises the steps of:

receiving the second packet communications session state information in response to the step of forwarding;

adjusting connection bandwidth associated with the first packet communications session to match connection bandwidth associated with the second packet communications session;

providing computer system address information to the data storage system so that the data storage system can establish a route to the computer system; and

using the first packet communications session between the computer system and the data communications device and the second packet communications session between the data communications device and the service processor associated with the data storage system to perform packet communications between the computer system and the service processor associated with the data storage system.

Though Wookey (507) does not go into great detail describing the connection process, he does disclose that the connection is secure and authenticated. From this

knowledge, one skilled in the art would recognize that communications session state information would be available to all the communicating parties. This information typically includes such data items as the addresses of the computers and the connection bandwidth. It is inherent that the bandwidth must be adjusted to a uniform rate to prevent lost packets. If one computer is sending packets faster than the other computer is prepared to receive them, the information is simply lost. It is also inherent that since all the computers involved in the communications need to know the addresses of the other computers, providing the computer system address information to the data storage system is a necessity. Finally, it is inherent that after all the time taken to set up a secure communications channel, that the channel would be used to perform packet communications between the computer system and the service processor associated with the data storage system.

With respect to claim 17, Wookey (507) discloses the method of claim 1 wherein the step of receiving a request to initiate a communications session with the data storage system further comprises the steps of:

receiving a service ticket from the data storage system; and (Col. 3, Lines 40-45) analyzing the service ticket to determine an identity of the data storage system to which a packet communications session is to be established from the computer system.

(Col. 3, Lines 62-67; Col. 4, Lines 1-3)

Wookey (507) discloses how the customer systems periodically perform a variety of diagnostic tests and transmit the results to the remote service center. Though he

does not use the phrase "service ticket," the functionality is the same. It is well known to those in the computing art that data transmitted from one computer to another (such as a service ticket) will contain information regarding the origin of the data. Because Wookey (507) discloses a database of customer information, including the history of "diagnostic tests and patches that exist for a particular product" (Col. 4, Lines 66-67), the diagnostic information must be associated in the database to whatever customer system generated the information. Thus, it is inherent that any diagnostic information transmitted to the service center can be analyzed to determine its origin. Since this information includes "error messages from log files, system crash data" etc. (Col. 3, Lines 63-64), the staff at the service center will know when to initiate communications to the customer system.

With respect to claim 18, Wookey (507) discloses the method of claim 1 wherein the steps of establishing a first packet communications session, establishing a second packet communications session, and performing packet communications are performed using secure and authenticated communications sessions. (Col. 10, Lines 55-60)

With respect to claims 19, 41, and 53, Wookey (507) discloses, in a processor in a data storage system a method for establishing a packet communications session with a computer system, the method comprising the steps of:

receiving a request to initiate a packet communications session, the request to initiate a packet communications session includes user authentication information of a user of the computer system; (Col. 1, Lines 37-40; Col. 9, Lines 5-7)

providing data storage system address information to an initiator of the request;
receiving computer system address information to allow the processor in the data
storage system to perform packet communications with the computer system;

establishing a packet communications session with the computer system based on the computer system address information; and (Col. 1, Lines 40-42)

authenticating an identity of the user based on the user authentication information in order to authorize the establishment of the packet communications session to the data storage system. (Col. 8, Lines 42-45)

Wookey (507) describes how a remote support engineer will initiate a dial-up connection to a computer to perform analysis and maintenance. Those skilled in the art will recognize that dial-up connections, like other Internet connections, are inherently packet-based. Because connection information (such as an IP address, modem phone number, and connection bandwidth) is required for packet communications, it is inherent that at some point the monitored site provides its address information. Similarly, it is inherent that at some point the monitored site will also receive address information from the computer at the service center.

Page 24

Wookey (507) describes in several places the use of authentication information to prevent unauthorized service center personnel from accessing the monitoring software installed at the monitored sites. Column 1, lines 38-43 show that this can be applied in such a way that the authorized service center personnel can log into the customer's system at the monitored site to troubleshoot errors that have been encountered.

With respect to claims 21 and 43, Wookey (507) discloses the method of claim 19 or 41, further comprising the steps of:

in response to the step of authenticating an identity of the user, the processor establishes a packet communications session with a data communications device from which the request to initiate a packet communications session originates. (Col. 4, Lines 12-16)

Wookey (507) discloses that some embodiments of the invention can include the use of the Internet. Those skilled in the computer networking art will recognize that communications over the Internet will require that the data pass through at least one router (data communications device) between its source and its destination. It is inherent that if the data is going through a router, at some point the source computer and destination computer will both have to establish packet communications sessions with the router.

Application/Control Number: 10/036,333

Art Unit: 2132

With respect to claims 22, 44, 51, and 55, Wookey (507) discloses the method of claim 21, 43, 50, or 53 wherein the processor is a service processor in the data storage system and the data storage system address information is a pre-configured network address assigned to the service processor associated with the data storage system by a vendor of the data storage system. (Col. 3, Lines 56-59; Col. 4, Lines 12-16)

In column 3, Wookey (507) describes a master monitoring computer at each monitored site, and that this master computer collects the diagnostic information for each monitored computer on the network. This system can be seen in Wookey's figure 1. This is analogous to the service processor of the data storage system, which is depicted in applicant's figure 3 as a computer connected to the data storage system. In regards to the second limitation of the claims, those skilled in the computer arts would know that in Internet communications, every computer has a pre-configured network address assigned to it, known as its IP address.

With respect to claims 23 and 45, Wookey (507) discloses the method of claim 19 or 41 wherein:

the request to initiate a packet communications session is sent from a data communications device interconnected with the computer system; and (Col. 4, Lines 12-17)

wherein the step of providing data storage system address information provides a network address of the processor in the data storage system to the data

Art Unit: 2132

communications device for receipt by the computer system to allow the computer system to perform packet communications to the data storage system. (Col. 4, Lines 12-17)

Wookey (507) discloses that, "for embodiments in which the internet is used to transmit diagnostic results, the monitored system initiates provision of the diagnostic results without any intervention of the service center." In other words, the monitored system initiates communications over the Internet to the service center. As previously discussed, communications over the Internet necessitate that the data crosses one or more routers between its source and its destination. Thus, when the monitored system is attempting to establish communications with the service center, it sends a request to a router, and the router forwards the request to the service center. Also as previously mentioned, communications between two computers inherently include the transmission of address information for each computer. In communications over the Internet, this would be the IP address (i.e. the network address) of each computer.

With respect to claims 24 and 46, Wookey (507) discloses the method of claim 19 or 41 the step of establishing a packet communications session with the computer system establishes route information within the data storage system based on the computer system address information to allow the processor o perform packet communications with the computer system. (Col. 4, Lines 12-17)

Application/Control Number: 10/036,333

Art Unit: 2132

Though Wookey (507) does not go into great detail about the connection process, those skilled in the art will realize that communications over the Internet include packet routing information to ensure that no data is lost en route.

In regards to claim 57, Wookey (507) discloses the system of claim 56 wherein:

the computer network other than the vendor computer network is a customer computer network; (Figs. 1 and 4)

the data storage system is coupled to the customer computer network; (Figs. 1 and 4)

the connection process is operated by a vendor support engineer in order to provide remote support to the data storage system on the customer computer network; and (Col. 8, Lines 42-45)

the second packet communications session is established from the data communications device to a service processor associated with the data storage system to allow the support engineer operating the connection process to remotely maintain the data storage system using the first and second packet communications sessions. (Col. 8, Lines 42-45)

Wookey (507) discloses in column 8 that, "it is possible to protect each monitor with a unique password so that only authorized administrative personnel can access a given monitor for modification." This implies that those administrative personnel from the service center who are authorized to access a monitor at a customer site are

allowed to establish communications via some communications process. Thus, the service personnel are operating a communications process (such as a telnet or ssh connection) to establish communications to the monitored site. Wookey's figures 1 and 4 show a monitored site consisting of a master monitor and a plurality of connected computers. Because a computer will always store some kind of data somehow (whether in a hard drive or in RAM), any computer is a data storage system. Thus, we have personnel from the service center operating a communications process to perform packet communications with a data storage system.

With regards to claims 59 and 60, Wookey (507) discloses the computer system of claim 18 or 40 wherein a security client is activated on said service processor to block out TCP data packets that have not been encrypted by a predetermined gateway server. (Col. 10, Lines 3-8; It is inherent that if data received at either end of the communications link is not encrypted with the proper dynamic key, that data will be ignored. As previously stated, communications between computers are widely known in the art to be packet-based.)

## Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

<sup>(</sup>a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Art Unit: 2132

Claims 61-63 are rejected under 35 U.S.C. 103(a) as being unpatentable over .

Wookey (US Patent #6,023,507).

With regards to claims 61-63, Wookey does not expressly disclose the method of claim 1, 25, or 47 wherein said establishing a first packet communications session comprises establishing a first Internet Protocol (IP) digital packet communications session. However, at the time of the invention, digital modems (such as cable modems) were known in the art. Thus, it would have been obvious to one skilled in the art to use digital communications to transfer monitored system information from the monitored system to the service center.

#### Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Virgil Herring whose telephone number is (571) 272-8189. The examiner can normally be reached on Monday-Friday.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Gilberto Barron can be reached on (571) 272-3799. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Application/Control Number: 10/036,333 Page 30

Art Unit: 2132

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Virgil Herring ∨ µ Examiner Art Unit 2132

VH

SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2100